



From:
Trace Analytics, LLC
15768 Hamilton Pool Road
Austin, Texas 78738

800-247-1024 • 512-263-0000
Fax 512-263-0002
E-mail service@AirCheckLab.com

Report 15-06714, Sampled on
3/10/2015

Next Sample Due Quarterly, Approximately
6/10/2015

To:
Total Diving
6356 Sherbrooke West
Montreal, QC H4B 1M9
CANADA

AIR STATION
IS IN COMPLIANCE WITH THE AIR/GAS QUALITY PORTION OF THE SPECIFICATION:
CSA STANDARD Z275.2-2011 OCCUPATIONAL SAFETY CODE FOR DIVING OPERATIONS (H)
AS ANALYZED AND REPORTED ON THIS CERTIFICATE
FOR THE SAMPLE DESCRIBED UNDER SECTION "SAMPLE & REPORT INFORMATION"



American Assn for Laboratory Accreditation
1991: Certificate No. 322.01 Chemical Field of Testing

R. A. Smith

Richard A. Smith, Laboratory Director

Analytical Test Methods	Media Sampled	Estimate of Uncertainty
Gases & Vapors CAT-A-01 Gas Chromatography/Mass Spectrometry	Source Bottle: 745331	The average analytical uncertainty (k=2) is 98.8±2.4% (relative) at the specification limit for the ten compounds normally reported. For uncertainty information for a specific compound, contact Trace.
Oil & Particulate CAT-A-03 Analytical Gravimetry	Ambient Bottle: N/A	
Particle Size CAT-A-04 Optical Microscopy	Source Filter: 3409	

Results relate only to items tested. This report shall not be reproduced except in full without the written permission of Trace Analytics, LLC
© Copyright 2015, Trace Analytics, LLC

Sample & Report Information

Results of Test: PASS

Sampled For	Air Station	Analytes	Source Results	Ambient Results	Specification ¹ Allowable Limits
Sampled By	Joseh Allan	Oxygen, Volume %	21.0	N/A	20-22
Sampled On	3/10/2015	Nitrogen, Volume %	78.2	N/A	N/A
Received On	3/12/2015	Argon, Volume %	0.8	N/A	N/A
Analyzed On	3/13/2015	Nitrogen Plus Argon, Volume %	79.0	N/A	78-80
Sampled From	Compressor	Carbon Monoxide (CO), ppmv	<0.3	N/A	3
Make	Jordair	Carbon Dioxide (CO ₂), ppmv	427	N/A	600
Model	K15-3EV	Water Content (H ₂ O), ppmv/Dewpoint, °F	<3.4 / <-91	N/A	27 / -63 (W)
Serial No.	82/23/6/01	Atmospheric Dew Point, °F (DT)	Not Provided	N/A	N/A
Cylinder(s)	4	TVHC (including CH ₄), ppmv	2.5	N/A	15
		Methane (CH ₄) ppmv	2.5	N/A	10
		TVHC (excluding CH ₄), ppmv	<0.7	N/A	5
		Oil (condensed) & Particulate, mg/m ³	<0.04	N/A	0.1
Hours	2987	Odor (provided by customer)	None/Slight	N/A	None/Slight
Sample Phase	Before Filter Change	Halogenated Hydrocarbons, ppmv	<0.1	N/A	5
Customer Comments		Atmospheric Dewpoint, °C	<-68	N/A	-53
		Pressure Dewpoint, °C	<-53	N/A	-5°C

PASS

(H) Compressed breathing air in cylinders and piping ≥ 15.3 MPa (2216 psig) shall have an atmospheric dew point ≤ -53°C (-63°F) or water vapor ≤ 27 mL/m³ (ppm) and SHOULD have a pressure dew point ≤ 5°C (9°F) below the lowest temperature to which the cylinder or piping can be exposed during any time of the year at that geographic location. If an operating pressure is not provided, we will use 20.7 MPa (3000 psig).
(W) Dew point is expressed in °F at one atmosphere pressure absolute.
(DT) Atmospheric Dew Point, °F. 'Not Provided' means Detector Tube data was not provided on the Data Sheet, incomplete or taken incorrectly.

Report Number 15-06714
Customer ID 2292
Date Reported 3/16/2015
Frequency Quarterly
Next Sample Due Approx. **6/10/2015**