



# Polyureseal BP Gloss and satin

## PRODUCT NUMBER AND CONTAINER SIZE

50206 Qt/50106 Gal/50306 5g pail  
SATIN

**WATER BASED/COVERAGE:** One gallon covers approximately 350-500 square feet. 50286 Qt/50186 Gal/50386 5g pail

**DESCRIPTION:** Safecoat® Polyureseal BP is one of the highest quality low toxicity water-based clear gloss finishes available today. Its exceptional durability and abrasion resistance, coupled with high solids, very low VOC and low odor, make it the clear alternative to conventional solvent and water-based polyurethanes in performance without the toxicity. Also available in satin.

**USE ON:** Safecoat® Polyureseal BP can be used on unfinished (or properly prepared and sanded previously finished) wooden surfaces such as floors, furniture and cabinetry, and is excellent for gym floors and auditoriums.

**SURFACE PREPARATION:** All surfaces must be clean and free from dirt, dust, grease, wax, oil, silicone, tsp/soap, mill scale, oxidation, loose peeling paint or varnish, or any foreign matter/contaminants. Apply test patches before undertaking large areas to assure good adhesion and lack of surface contamination. Wood staining should be completed before applying finish coats. Sand wood with the grain only. When surfaces have been sanded, dust and vacuum thoroughly to remove debris and then use a damp rag to remove dust before applying finish coats. Wood surface may be dampened to raise grain, sanded, and then wiped free of dust before applying stain or finish. Moisture content of wood should be below 12% for best results. To achieve a satin finish on wood, apply multiple thin coats of Safecoat Polyureseal BP Gloss until the surface is completely sealed, followed by one final coat of Satin.

**APPLICATION:** Always have adequate ventilation. Intermix (boxing) all containers of the same sheen to ensure gloss uniformity before applying. Before using, mix coating thoroughly by gently stirring or rolling container to avoid air bubbles. Be sure to stir product thoroughly every 20 minutes during application. Do not shake container. Pour material to be used into another container before applying coating to avoid contaminating main container. Then apply as is, using a quality nylon brush, pad applicator, or unheated spray applicator. Apply liberal coats, keeping a good wet edge and avoid overbrushing. In most cases, a minimum of 3 coats is required, depending on the surface. When spraying, use a .015 tip or smaller. Apply thin even coats when spraying rather than heavy coats which will tend to sag. If spray pattern begins to dryspray, reduce air pressure and increase material flow to surface. Use a damp, dust free rag after sanding to remove dust particles. Use aluminum oxide or silicon carbide sandpaper to sand between coats. For best results, this product should not be reduced. Use only during low or moderate humidity conditions. Applying this product over lightly dampened surfaces can assist the

user in controlling the dry time. Smoother finishes are achieved when surfaces are damp during application. Note: these instructions are intended to be general only and not exhaustive. The applicator should determine which preparation and techniques are best suited to the specific surface.

**COVERAGE:** One gallon of Safecoat Polyureseal BP covers approximately 350 square feet in one coat depending on method of application and surface porosity.

**CLEAN-UP:** Clean tools and equipment while they are still wet with a solution of SafeChoice Super Clean and warm water.

**DRYING/CURING TIME:** Under normal conditions, Safecoat® Polyureseal BP dries to touch in one hour, is sandable after 2 - 4 hours, and re-coatable after 4 - 8 hours. The product will continue to cure and become harder over time. Avoid traffic for at least 24 hours after application. Normal conditions include a dry surface, access to fresh airflow, moderate humidity, and temperatures around 70°F. Thick application, high humidity or conditions other than normal will cause Safecoat Polyureseal BP to dry and cure more slowly.

**MAINTENANCE:** Damp mop or wipe coated surface periodically with clean water or an odorless, dye-free, non-volatile all purpose cleaner like SafeChoice Super Clean.

**LIMITATIONS:** Unlike conventional finishes, Safecoat finishes are made without formaldehyde preservatives or toxic mildewcides or fungicides. Do not contaminate. Store in airtight containers. Do not use when indoor or surface temperature is below 55°F. Do not freeze. Note that even after full product cure, the finish can be scratched by animal claws, sharp edged furniture, and similar items. Care should be taken to minimize exposure to such conditions.

**HEALTH PRECAUTIONS:** As with all coatings and sealers, keep container tightly closed and out of the reach of children. Do not take internally. Always use adequate ventilation. Wear a mask when sanding and avoid breathing sanding dust. AVOID CONTACT WITH SKIN AND EYES AND AVOID BREATHING OF SPRAY VAPORS AND SPRAY MIST. If you are chemically sensitive, always test for personal tolerance.

### PHYSICAL DATA:

Physical Description:	Viscous milky liquid
% Volatile by Volume:	71.25%
Solubility in Water:	Dilutable
% Volatile by Weight:	67.68%
VOC Material:	114 g/l
VOC Material less H2O:	283 g/l
HAP's (Hazardous Air Pollutants)	zero

## If you are chemically sensitive, always test for personal tolerance.

**LIMITED LIABILITY:** Liability, whether express or implied, is limited solely to replacement of product shown to be defective when applied in accordance with instructions and shall under no circumstances include liability for labor costs or consequential damages. It is the user's responsibility to determine the suitability and safety of the product for its intended use. This limited warranty may not be modified or extended by manufacturer's representatives, distributors, or dealers of AFM products. We particularly recommend that users always test in small inconspicuous areas before application to the entire surface.